

SIGN SUMMARY TELESCOPING PERFORATED TUBES

REGION	STATE	LOCAL PROJ. NO.	SHEET NO.
8	ND.	F-1-094(03)	53

Station	Location	Sign No. or Assembly No.	Sign Area		Sign Supports			Anchorage Unit					Total Support Weight	Reset Sign Panel	Reset Sign Support		
			Flat Sheet S. F.	Panel S. F.	Post Dimensions Length 1st 2nd	Sleeve Dimensions Size In.	Length 1st 2nd	Size In.	Post 1st 2nd Size	Rein. Sleeve Length Size							
1+25 Rt.	Business Loop	5 (RS)	6.93		10.0		2 1/2			4.0		2 1/2	.5	3	43.88		
6+00 Lt.	"	20 (WS)	9.00		10.0		2 1/2			4.0		2 1/2	.5	3	43.88		
7+00 Rt.	"	11 (RS)	12.00		10.0	10.0	2 1/2			4.0	4.0	2 1/2	(2).5	3	87.77		
9+00 Rt.	"	11 (RS)	12.00		10.0	10.0	2 1/2			4.0	4.0	2 1/2	(2).5	3	87.77		
46+91 Lt.	"	R8-3-36	9.00		Light Standard		Mounted										
47+00 Rt.	"	16 (RS)	9.00		13.0		2 1/2	3.0		2	4.0		2 1/2	.5	3	59.45	
50+85 Lt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
52+70 Lt.	"	R8-3-36	9.00		Light Standard		Mounted										
52+70 Rt.	"	16 (RS)	9.00		13.0		2 1/2	3.0		2	4.0		2 1/2	.5	3	59.45	
52+80 Lt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
54+82 Lt.	"	R2-1-36	12.00		Light Standard		Mounted										
54+82 Rt.	"	11 (RS)	12.00		13.5	14.0	2 1/2				4.0	4.0	2 1/2	(2).5	3	108.56	
56+94 Lt.	"	R8-3-36	9.00		Light Standard		Mounted										
57+00 Rt.	"	16 (RS)	9.00		13.0		2 1/2	3.0		2	4.0		2 1/2	.5	3	59.45	
59+06 Lt.	"	W1-2(6)36	9.00		Light Standard		Mounted										
62+50 Rt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
63+30 Lt.	"	R8-3-36	9.00		Light Standard		Mounted										
63+30 Rt.	"	16 (RS)	9.00		13.0		2 1/2	3.0		2	4.0		2 1/2	.5	3	59.45	
63+80 Lt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
66+35 Lt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
66+70 Rt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
67+54 Lt.	"	R8-3-36	9.00		Light Standard		Mounted										
67+54 Rt.	"	16 (RS)	9.00		13.0		2 1/2	3.0		2	4.0		2 1/2	.5	3	59.45	
67+85 Lt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
69+25 Rt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
70+85 Rt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
71+00 Rt.	"	Assembly D	12.13		14.5		2 1/2	4.5		2	4.0		2 1/2	.5	3	67.23	
71+79 Lt.	"	R8-3-36	9.00		Light Standard		Mounted										
72+00 Rt.	"	16 (RS)	9.00		13.0		2 1/2	3.0		2	4.0		2 1/2	.5	3	59.45	
72+90 Lt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
73+30 Rt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
74+35 Lt.	"	Assembly A	6.00		12.0		2				4.0		2 1/2	.5	2 1/2	41.66	
75+10 Rt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
75+15 Rt.	"	Assembly A	6.00		12.0		2				4.0		2 1/2	.5	2 1/2	41.66	
76+03 Lt.	"	R8-3-36	9.00		Light Standard		Mounted										
76+03 Rt.	"	16 (RS)	9.00		13.0		2 1/2	3.0		2	4.0		2 1/2	.5	3	59.45	
76+35 Lt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
76+75 Rt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
79+60 Rt.	"	1 (RS)	5.18		12.5		2 1/2				4.0		2 1/2	.5	3	50.82	
79+85 Lt.	"	R3-9b-36	12.00		Light Standard		Mounted										
79+85 Rt.	"	11 (RS)	12.00		13.5	14.0	2 1/2				4.0	4.0	2 1/2	(2).5	3	108.56	
Subtotal			324.76												1809.42		

SIGN SUMMARY TELESCOPING PERFORATED TUBES

FHWA REGION	STATE	FED AID PROJ NO	SHEET NO
8	ND.	F-1-09A(03)	54

Station	Location	Sign No. or Assembly No.	Sign Area		Sign Supports				Anchorage Unit				Total Support Weight	Reset Sign Panel	Reset Sign Support	
			Flat Sheet S. F.	Panel S. F.	Post Dimensions Length 1st 2nd	Sleeve Dimensions Size In.	Post 1st 2nd	Rein. Sleeve Length Size								
81+65 Rt.	Business Loop	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
81+97 Lt.	"	R8-3-36	9.00		Light Standard Mounted											
82+00 Rt.	"	16 (RS)	9.00		13.0		2 1/4	3.0	4.0		2 1/2	.5	3	59.45		
82+35 Rt.	"	Assembly A	4.50		12.0		2		4.0		2 1/2	.5	2 1/2	41.66		
82+40 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
82+65 Rt.	"	Assembly A	4.50		12.0		2		4.0		2 1/2	.5	2 1/2	41.66		
84+60 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
86+00 Rt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
86+21 Lt.	"	R8-3-36	9.00		Light Standard Mounted											
86+21 Rt.	"	16 (RS)	9.00		13.0		2 1/4	3.0	4.0		2 1/2	.5	3	59.45		
86+25 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
87+65 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
89+85 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
92+68 Lt.	"	R8-3-36	9.00		Light Standard Mounted											
92+68 Rt.	"	16 (RS)	9.00		13.0		2 1/4	3.0	4.0		2 1/2	.5	3	59.45		
93+95 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
97+02 Lt.	"	R8-3-36	9.00		Light Standard Mounted											
97+02 Rt.	"	16 (RS)	9.00		13.0		2 1/4	3.0	4.0		2 1/2	.5	3	59.45		
97+60 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
99+14 Lt.	"	R2-1-36	12.00		Light Standard Mounted											
99+30 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
100+00 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
101+10 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
101+50 Rt.	"	16 (RS)	9.00		13.0		2 1/4	3.0	4.0		2 1/2	.5	3	59.45		
102+50 Rt.	"	11 (RS)	12.00		13.5	14.0	2 1/4		4.0	4.0	2 1/2	(2).5	3	108.56		
103+00 Lt.	"	R8-3-36	9.00		Light Standard Mounted											
103+10 Rt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
103+15 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
104+00 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
104+00 Rt.	"	16 (RS)	9.00		13.0		2 1/4	3.0	4.0		2 1/2	.5	3	59.45		
105+12 Lt.	"	R3-9b-36	12.00		Light Standard Mounted											
105+12 Rt.	"	11 (RS)	12.00		13.5	14.0	2 1/4		4.0	4.0	2 1/2	(2).5	3	108.56		
106+00 Rt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
107+24 Lt.	"	R8-3-36	9.00		Light Standard Mounted											
107+24 Rt.	"	16 (RS)	9.00		13.0		2 1/4	3.0	4.0		2 1/2	.5	3	59.45		
108+80 Lt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
109+20 Rt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	50.82		
111+50 Lt.	"	Assembly A	6.00		12.0		2		4.0		2 1/2	.5	2 1/2	41.66		
112+00 Rt.	"	1 (RS)	5.18		12.5		2 1/4		4.0		2 1/2	.5	3	30.82		
112+05 Rt.	"	Assembly A	6.00		12.0		2		4.0		2 1/2	.5	2 1/2	41.66		
113+56 Lt.	"	R8-3-36	9.00		Light Standard Mounted											
113+56 Rt.	"	16 (RS)	9.00		13.0		2 1/4	3.0	4.0		2 1/2	.5	3	59.45		
Subtotal			302.42											1824.94		