

DESIGN DATA

Traffic

Average Daily
Current (1990) 12,900 Pass. 700 Trucks 13,600 Total 1360.
Forecast (2010) 15,950 Pass. 850 Trucks 16,800 Total 1680.

Est. 30th
Max. Hr.

Design Speed 35 MPH


Traffic Classification "M"

Minimum Sight Distance (Stopping) 250'

Minimum Sight Distance (Safe Passing)

Minimum Passing Sight Distance for Marking

Bridges HS 20

MANDAN
Sec. 31, Twp. 139N, Rge. 81W

Bid opening Sept 21, 90
Begin work Nov. 1±, 90
April 120 days later
May 1 to 6 mos later
\$550,000/dad
\$550,000/dad
\$550,000/dad
= The intersection of Memorial Highway and 46th Ave. SE in Mandan

PRELIMINARY

Date May 30, 1990

NORTH DAKOTA
DEPARTMENT OF TRANSPORTATION

JOB#

FMRA REGION	STATE	PROJECT	SELECT NO.
8	N.D.	IR-194-4(053)000 F-1-094(007)920	1

GOVERNING SPECIFICATIONS:

Standard Specifications adopted by the North Dakota State Highway Department November 1986, Standard Drawings currently in effect, and other Contract Provisions submitted herein.


LENGTH OF PROJECT

PROJECT	Miles-Gross	Miles-Net
IR-194-4(053)000	0.415	0.415
F-1-094(007)920	0.396	0.396
TOTAL	0.811	0.811

BISMARCK

Sec. 5, Twp. 138N, Rge. 80W

SPMT. MRK



GENERAL NOTES

FHWA REGION	STATE	FED. AID PROJ NO	SHEET NO
8	N.D.	F-1-094(007)920	

754 IN-PLACE SIGNS: The district shall inspect the in-place signs
030 and supports for condition to determine if there are any additional signs or supports that can be reset or changed to new sign and supports. The district shall inform the contractor of any changes prior to the time the contractor orders materials.

754 SIGN SUPPORTS: The sign support "Steel Galvanized Posts - Square
050 Tube Perforated" were designed using a minimum yield strength of 42,000 psi and the design requirements of the "Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals." The wind speed of 75 mph was used. The contractor may choose other types of square telescoping steel post in lieu of the ones specified but the contractor must provide equivalent strength posts and meet the FHWA yielding support requirements.

770 OVERHEAD LINES CLEARANCE: Minimum horizontal and vertical
001 clearance between light and/or signal standards and power lines shall be as shown for the following power line voltages:

Power Line Voltage	* Horizontal Clearance	Vertical Clearance
0-15,000	5'	6'
15,000-50,000	5'	7'
50,000 Plus	5'+0.033' per KV	7'+0.033' per KV
	Over 50 KV	Over 50 KV

770 SODIUM VAPOR LUMINAIRE (MOUNTED ON EXISTING STANDARDS): The item
034 sodium vapor luminaire shall consist of installing the new high-pressure sodium vapor luminaire on the existing light standard. The existing light standard shall remain in place. The contractor shall make the necessary connections between the new high-pressure sodium vapor luminaire and the existing light standard conductor.

The item sodium vapor luminaire will be measured by the number installed. The quantities measured will be paid for at the contract price and shall be full compensation for all labor, equipment, and materials necessary to complete the installation.

770 REMOVE STREET LIGHT LUMINAIRE: The item remove street light
043 luminaire shall consist of removing the existing luminaires from their present locations. The contractor shall arrange with the local utility company to have the circuits disconnected from the source of live power. The conductor leading to the luminaire shall be disconnected. The luminaire shall be removed without damage to the luminaire or wiring. The existing light standards shall remain in place. The removed luminaires shall be loaded, hauled, and stored at a point not further than three (3) miles from the project as designated by the engineer. The contractor shall be responsible for any damage to the luminaire and shall replace, at the contractor's expense, any damaged luminaires. The removed luminaires shall be the property of the state. The item remove street light luminaire will be measured by the "Number of Luminaires Removed." The quantities measured will be paid for at the contract price and shall be full compensation for all labor, equipment, and material necessary to complete the removal and storage.

770 LUMINAIRES: The high-pressure sodium vapor luminaires shall be
700 internal ballast-constant wattage, 120x240 voltage, operated on 120 volts.

770 LEGEND - LIGHTING:
750

250-watt sodium vapor luminaire

400-watt sodium vapor luminaire

770 RELOCATE LIGHT STANDARD: After erection, the contractor shall
P01 touch up all marred or scratched areas with material conforming to Section 854.

770 EXISTING PLANS: As-built plans of existing lighting system are
P02 available for inspection at the North Dakota Department of Transportation, Bismarck District Office.

GENERAL NOTES

FHWA REGION	STATE	FED. AID PROJ NO	SHEET NO
8	N.D.	F-1-094(007)920	


- 770 RELOCATE CONCRETE LIGHT STANDARD: The item, "Relocate Concrete Light Standard" shall consist of removing light standard from existing location designated on the plans. The contractor shall arrange with the local utility company to have the light circuits disconnected from the source of live power at the feed point. Wires leading to the luminaire receptacle shall be disconnected at the fuses and light standard removed. All standards shall be plumbed. Mast arms shall be perpendicular to the centerline of the roadway to be lighted unless shown otherwise on the plans. The contractor shall be responsible for any damage to the poles, luminaires, mast arms, internal wiring and fuses, and shall replace at his own expense any damaged equipment. The item "Relocate Concrete Light Standard" will be measured by the number of light standards relocated. The quantities measured will be paid for at the contract price and shall be full compensation for all labor, equipment and materials necessary to complete the relocation of light standards.
- 772 EXISTING PLANS: As-builts plans of existing traffic signal system are available for inspection at the North Dakota Department of Transportation, Bismarck district office.

- 772 PAINT: The traffic signal system components shall be painted in accordance with the following:

Transformer base - green
Mast arm - green
Signal head mounting hardware - green
Shaft - green
Signal housing - green
Pedestrian pushbutton post - green

- 772 MICROLOOP DOUBLE PROBE SET: The microloop probe shall be a small cylindrical passive transducer of earth's vertical magnetic field intensity into inductance. It transforms changes in magnetic field intensity into inductance changes which can be sensed by loop detector units. Probes shall fit vertically in 1" holes and lead-in cable in 3/8" saw slot. Microloop probes can be connected in series with other microloop probes or conventional wire loops. The microloop probe shall operate under the following parameters: Earth's Vertical Magnetic Field (0.2 to 1.0 oersted), Inductance (20 mH to 25 m per probe plus 20 mH per 100' of wire), DC Resistance (0.5 ohms per probe plus 3.2 ohms per 100' of wire), Transducer Gain (typically 3.5 mH per oersted at 0.4 OE ambient vertical field intensity), and Sensitivity with 2 probes (7.0 mH per oersted at 0.4 OE ambient vertical field intensity). The microloop probes shall operate at a temperature range of -35°F to +165°F (-37°C to +74°C) and at humidity of 0 to 100%. The microloop probes shall detect all motorized vehicles registered in the state of North Dakota.

FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	L-1



STATION		CONDUIT RUNS		CABLE TRENCH		CABLE RUNS		FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
		Length	Size	Length	Length	Type					
177+73-352'	Rt. to				26'	(A) 744'	(2) No. 6 Type RHW				
177+53-335'	Rt. to				230'	(B) 372'	(1) No. 6 Type THW				
177+81-111'	Rt. to				46'						
178+27-111'	Rt. to				8'						
178+32-100'	Rt. to										
178+40-100'	Rt.	12'	2"								


QUANTITIES				
Cable Trench-Type I	2 Inch Dia. Rigid Conduit	Underground Conductor No. 6 Type RHW	Underground Conductor No. 6 Type THW	
LF	LF	LF	LF	
310	12	744	372	

- (A) 100 ft. of conductor for providing wiring of overhead sign structure from foundation to load center.
- (B) 50 ft. of conductor for providing wiring of overhead sign structure from foundation to load center.

NO.	STATION	OFFSET	WATTAGE	CIRCUIT	IES-TYPE	POLE HT.	MAST ARM

TRAFFIC CONTROL SYSTEM
Lighting Quantities
Memorial Highway
Mandan, ND

FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	L-3



RELOCATE LIGHT STANDARD

Existing Location	New Location
Sta. 179+26-24' Rt.	179+00-53' Lt. 1 EA
Sta. 181+30-20' Rt.	180+80-33' Rt. 1 EA

FEED POINT - COMBINATION LTG. & SIG. - PAD MTD.

Sta. 179+50-94' Rt. 1 EA

TRAFFIC CONTROL SYSTEM
Lighting Layout

Memorial Highway
Mandan, ND

STATION		CONDUIT RUNS		CABLE TRENCH	CABLE RUNS				FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
		Length	Size	Length	Length	Type			8	N.D.	IR-194-4(053)000	L-4
	178+40-100' Rt. to 179+50-94' Rt.			109'	240' 120'	(2) No.6 Type RHW (1) No.6 Type THW						
	179+50-94' Rt. to 179+50-36' Rt. to 179+79-36' Rt.				(E)394' (F)197'	(2) No.6 Type RHW (1) No.6 Type THW						
	179+50-94' Rt. to 179+50-36' Rt. to 179+96.5-33' Rt. to 180+80-33' Rt. to 182+00-33' Rt.	(G)85' (G)123'	2" 2"	57' 47'	666' 333' 333'	(2) No.2 Type RHW (1) No.4 Type RHW (1) No.6 Type THW						
	179+50-94' Rt. to 179+50-36' Rt. to 179+00-40' Rt. to 179+00-53' Lt. to 179+96.5-48' Lt. to 182+00-37' Lt.	92' (G)196'	2"	50' 96'	1028' 514'	(2) No.4 Type RHW (1) No.6 Type THW						

QUANTITIES											
Concrete Foundation Highway Lighting	Concrete Foundation Feed Point - Type B	Cable Trench - Type I	2 Inch Dia. Rigid Conduit	Underground Conductor No. 2 - Type RHW	Underground Conductor No. 4 - Type RHW	Underground Conductor No. 6 - Type THW	Underground Conductor No. 6 - Type THW	H.P. Sodium Vapor Luminaire 250 Watt	Relocate Light Standard	Remove Street Light Luminaires	Feed Point - Combo LTG. & SIG. - Pad MTD. - Type I
EA	EA	LF	LF	LF	LF	LF	LF	EA	EA	EA	EA
1	1	359	92	666	1361	634	1164	2	2	2	1

- (E) 200 ft. of conductor for providing wiring of overhead sign structure from foundation to load center.
 (F) 100 ft. of conductor for providing wiring of overhead sign structure from foundation to load center.
 (G) 2" Dia. bridge mounted conduit shall be installed by structural contractor.
 (H) Relocated light standard.

NO.	STATION	OFFSET	WATTAGE	CIRCUIT	IES-TYPE	POLE HT.	MAST ARM
1	179+00	53' Lt.	250	1	MSC IV	(H)	
2	180+80	33' Rt.	250	1	MSC IV	(H)	

TRAFFIC CONTROL SYSTEM
 Lighting Quantities
 Memorial Highway
 Mandan, ND

FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	L-5

F-1-094(007)920

N

RELOCATE LIGHT STANDARD

Existing Location
Sta. 183+10-20' Rt.
Sta. 184+99-20' Rt.

New Location
Sta. 182+80-33' Lt.
Sta. 185+00-20' Rt.


1 EA
1 EA

REMOVE FEED POINT

Sta. 182+86-21' Rt. 1 EA

REMOVE WOOD POLE

Sta. 182+86-21' Rt. 1 EA



REMOVE STREET LIGHT LUMINAIRE

Sta. 183+10-20' Rt. 1 EA
Sta. 184+99-20' Rt. 1 EA

H.P. SODIUM VAPOR LUMINAIRE - 250 WATT

Sta. 182+80-33' Lt. 1 EA
Sta. 185+00-20' Rt. 1 EA

TRAFFIC CONTROL SYSTEM
Lighting Layout

Memorial Highway
Mandan, ND

FHWA REGION	STATE	FED. AID PROJ. NO.	HEET NO.
8	N.D.	F-1-094(007)920	L-7

TRAFFIC CONTROL SYSTEM
Lighting Layout

Memorial Highway
Bismarck, ND


Sta. 3+80-52' Lt.
Existing Junction Box In Place
to Remain.

Existing Conduit and
Conductor In Place to Remain

Sta. 4+48-75' Lt.
Existing Combo Signal &
Light Standard

Sta. 5+20-26' Lt.
Existing Combo Signal & Light
Std.

Existing Conduit
In Place to Remain



NOTE A: The contractor shall locate the existing conduit at Sta. 5+50-5' Lt. and salvage a sufficient length of conduit to make the necessary connection. The contractor shall be responsible for any damage to the existing conduit and shall replace any damaged conduit at his own expense.

RELOCATE LIGHT STANDARD

Existing Location	New Location	
Sta. 0+65-20' Rt.	0+65-24' Rt.	1 EA
Sta. 4+46-22' Rt.	4+36-32' Rt.	1 EA

RELOCATE CONCRETE LIGHT STANDARD

Existing Location	New Location	
Sta. 5+78-17' Rt.	Sta. 5+78-28' Rt.	1 EA

CONCRETE FOUNDATION - HIGHWAY LIGHTING

Sta. 5+78-28' Rt.	1 EA
-------------------	------

H.P. SODIUM VAPOR LUMINAIRE - 400 WATT

Sta. 2+59-24' Lt.	1 EA
-------------------	------

REMOVE STREET LIGHT LUMINAIRE

Sta. 2+59-24' Lt.	1 EA
-------------------	------

Sta. 7+04-29' Rt.
Existing Light Standard
In Place to Remain

STATION	CONDUIT RUNS		CABLE TRENCH	CABLE RUNS		FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
	Length	Size	Length	Length	Type				
-(0+40)-20' Rt. to 0+00-20' Rt. to 0+65-24' Rt.	(I) 64'	2"		230' 115'	(2) No.4 Type RHW (1) No.6 Type THW				8 N.D. F-1-094(007)920 L-8
3+80-52' Lt. to 4+36-32' Rt.	(J) 20'	2"	100'	270' 135'	(2) No.4 Type RHW (1) No.6 Type THW				
5+20-26' Lt. to 5+50-05' Lt. to 5+50-28' Rt. to 5+78-28' Rt. to 7+04-29' Rt.	33'	2"		747' 27' 124'	(3) No.4 Type RHW				

QUANTITIES									
Concrete Foundation Highway Lighting	Cable Trench-Type I	2 Inch Dia. Rigid Conduit- Bridge Mounted	Underground Conductor No. 4-Type RHW	Underground Conductor No. 6-Type THW	H.P. Sodium Vapor Luminaire 400 Watt	Relocate Light Standard	Relocate Concrete Light Standard	Remove Street Light Luminaire	
EA	LF	LF	LF	LF	EA	EA	EA	EA	
1	251	20	1247	250	1	2	1	1	


- (I) 2" dia. bridge mounted conduit shall be installed on structural plans.
 (J) 20 ft. of 2" dia. bridge mounted conduit from ground to light standard.
 (K) Existing light standard.

NO.	STATION	OFFSET	WATTAGE	CIRCUIT	IES-TYPE	POLE HT.	MAST ARM
#6	2+59	24' Lt.	400	2	MSC III	(K)	

TRAFFIC CONTROL SYSTEM
Lighting Quantities

Memorial Highway
Bismarck, ND


FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	L-9



TRAFFIC CONTROL SYSTEM

Combination Lighting & Signal Pad Mtd. Feed Point Detail

Memorial Highway
Mandan, ND



NOTE: The beacon head clearance above the roadway surface shall be 19'-0" \pm 6".



FLASHING BEACON - SPAN WIRE MOUNTED 1 EA.

* These items shall not be bid separately, but shall be included in the price bid for the item "Flashing Beacon Span Wire Mounted".

Sta. 164+03-53' Rt.
Install 45' Wood Pole
w/guys

Sta. 164+06-78' Rt.
Existing Wood Pole.
Install Switch Box,
Flasher, and Cabinet.

Sta. 164+11-57' Lt.
Install 45' Wood Pole
w/guys

*QUANTITIES										
1" Dia. Rigid Conduit	No. 12 AWG 3 Conductor Cable	1/8" Diameter Steel Galv. Stability Wire	3/8" Diameter Steel Galv. Span Wire	Beacon Heads	Flasher Mechanism	Switch Box and Cabinet	45' Wood Service Pole w/guy	Cable Hangers, ground rods, Mounting Hardware, and Entrance Heads	No. 8 Type RHW Conductor	
LF	LF	LF	LF	EA	EA	EA	EA	LS	LF	
77	158	114	114	4	1	1	2	1	90	


TRAFFIC CONTROL SYSTEM
Flashing Beacon Layout

Memorial Hwy. & 46th Av. S.E.
Mandan, ND

CONCRETE FOUNDATIONS-TRAFFIC SIGNAL

Sta. 176+30-65'	Lt.	1 EA
Sta. 176+82-21'	Lt.	1 EA
Sta. 177+07-20'	Rt.	1 EA
Sta. 177+33-35'	Rt.	1 EA

FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	F-1-094(007)920	S-3



NOTE: All stationing off eastbound roadway survey line.

Sta. 177+07-20' Rt.
Install Type IV Sign
Standard 20' Mast Arr

TRAFFIC CONTROL SYSTEM


Traffic Signal Layout

Memorial Hwy. & East Ramp
Mandan, ND

PULL BOX

Sta. 174+24-2' Lt.	1 EA
Sta. 176+97-65' Lt.	1 EA
Sta. 177+19-272' Rt.	1 EA
Sta. 178+97-17' Rt.	1 EA



FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	F-1-094(007)920	S-4



												FHWA REGION	STATE	FED A/O PROJ NO	PROJ NO
CONDUCTORS	CABLE 1 (12-12)			CABLE 2 (12-12)			CABLE 3		CABLE 4		CABLE 5				
Base	Tracer	Head	Indication	Head	Indication	Head	Indication	Head	Indication	Head	Indication	Head	Indication		
1 Black			Spare		Spare										
2 White			Neutral		Neutral										
3 Red		1,2,5,6	Red	3,4	Red										Neutral
4 Green			Ground		Ground										Neutral
5 Orange		1,2,5,6	Yellow	3,4	Yellow										Ground
6 Blue		1,2,5,6	Green	3,4	Green										Ground
7 White	Black		Spare		Spare										
8 Red	Black		Spare		Spare										
9 Green	Black		Spare		Spare										
10 Orange	Black		Spare		Spare										
11 Blue	Black		Spare		Spare										
12 Black	White		Spare		Spare										

MICROLOOPS

Loop No.	Type of Loop	Number of Probes	Saw Slot LF
1	Passage	2	--
2	Passage	2	8
3	Passage	2	8
4	Passage	2	--
5	Passage	2	--



Heads 1,2,3,4,
5, & 6
(12" Lenses)

ESTIMATED 19 ADT

TRAFFIC CONTROL SYSTEM
Heads, Conductors, Detector
Loops, & Traffic Volumes
Memorial Hwy. & East Ramp
Mandan, ND

STATION	CONDUIT RUNS		CABLE RUNS			FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
	Length	Size	Length	Type					
176+30-65' Lt. to 176+97-65' Lt. to 176+97-21' Lt.	110'	2"	116'	Cable 1					
176+82-21' Lt. to 176+97-21' Lt.	14'	1.5"	20'	Cable 2					
176+97-21' Lt. to 177+33-21' Lt. to 177+33-35' Rt.	91'	2.5"	101' 101'	Cable 1 Cable 2					
177+07-20' Rt. to 177+33-35' Rt.	28'	1.5"	44'	Cable 1					
174+24-02' Lt. to 175+74-2' Lt. to 175+74-18' Rt. to 176+85-50' Rt. to 177+33-35' Rt.	335'	2"	351'	Loop Lead In (2 & 3)					
177+19-272' Rt. to 176+90-55' Rt. to 177+33-35' Rt.	265'	2"	281'	Loop Lead In (1)					
178+97-17' Rt. to 177+95-49' Rt. to 177+75-37' Rt. to 177+33-35' Rt.	171'	2"	187'	Loop Lead In (4 & 5)					
177+33-35' Rt. to 177+75-37' Rt. to 177+95-49' Rt. to 179+63-80' Rt.	234'	2"	510' 255'	(2) No. 6 RHW (1) No. 6 THW					

TRAFFIC CONTROL SYSTEM
CONDUIT & CONDUCTOR QUANTITIES

MEMORIAL HWY & EAST RAMP
MANDAN, ND




CHART "A"

On Phase	Non-Conflicting Phase Allowed to Time Concurrently
1	Not Used
2	6
3	Not Used
4	None
5	Not Used
6	2
7	Not Used
8	Not Used

Blank Squares Denote a Red Indication.

*When one phase is on alone, any nonconflicting phase may start timing concurrently without a clearance interval. (See Chart "A")

TRAFFIC CONTROL SYSTEM
Controller Phasing
Memorial Hwy. & East Ramp
Mandan, ND

FHWA REGION	STATE	FED AID PROJ NO	Sheet #
8	ND	F-1-094(007)920	S-8

	Ø 1	Ø 2	Ø 3	Ø 4	Ø 5	Ø 6	Ø 7	Ø 8
BASIC INTERVALS (or FUNCTIONS)								
Initial Extension (Gap)		22.2 5.0		25.1 5.0		22.2 5.0		
Maximum (Maximum Green or Ext. Limit)		60		45		60		
Yellow Change		3.3		3.4		3.3		
Red Clearance		0.9		0.7		0.9		
Walk								
Pedestrian Clearance								
VOLUME DENSITY TIMING FUNCTIONS								
<u>Variable Initial Timing Options</u>								
Added Initial								
Minimum Initial		5.8		5.8		5.8		
Added Initial per Actuation		2.1		2.1		2.1		
Actuations Before Added Initial		2		2		2		
Computed Initial								
Minimum Initial		5.8		5.8		5.8		
Maximum Initial		22.2		25.1		22.2		
Actuations to Reach Maximum Initial		7.8		9.2		7.8		
Extensible Initial	NOT USED	USED	NOT USED	NOT USED	USED	NOT USED	NOT USED	NOT USED
Minimum Initial		5.8		5.8		5.8		
Maximum Initial	NOT	22.2	NOT	25.1	NOT	22.2	NOT	NOT
Added Initial per Actuation		2.1		2.1		2.1		
TIME WAITING GAP REDUCTION OPTIONS								
Passage Time		5.0		5.0		5.0		
Minimum Gap		1.4		1.4		1.4		
Time to Reduce to Minimum Gap		25.8		10.9		25.8		
Reduce Gap Every		1.0		1.0		1.0		
Reduce Gap Every Second By		0.1		0.3		0.1		
Reduce Gap By		3.6		3.6		3.6		
Locking Memory	X		X		X			
Non-Locking Memory								
Flashing-Normal & Conflict Monitor	Y		R		Y			
Start Up Phasing	G		R		G			
Type of Detector	Presence							
Loop	Calling*							
	Passage	X		X		X		


*Calling Loops shall place one call into the Controller on the Yellow or Red interval.
 Calling Loops shall be disconnected during the Green interval.

TRAFFIC CONTROL SYSTEM
 CONTROLLER SETTINGS


Memorial Hwy. & East Ramp
 Mandan, ND

FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	F-1-094(007)920	5-9

Note: After the installation and compaction of the aggregate base, the contractor shall trench a 4" trench and drill the 1" diameter holes. The microloop detectors shall be installed, embedded in the sand as shown. The aggregate base shall be recompacted to the density of the surrounding material and the microloops shall be tested for functional operational capacities prior to the PCC or Hot. Bit. Pavement placement.



PLAN



A - A



ELEVATION

TRAFFIC CONTROL SYSTEM
Microloop Detector Details

Memorial Hwy. & East Ramp
Mandan, ND


FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	F-1-094(007)920	S-10

NOTE: The contractor shall drill the 1 inch diameter holes, cut the saw slot in the existing hot bit. pavement and install the microloop detectors. The 1 inch diameter hole shall be filled with sand, seal the saw slot with sealant, and tested for functional operational capabilities prior to the placement of the 2 inch overlay.




Memorial Hwy & East Ramp
Mandan, ND

FHWA REGION	STATE	FED. AID PROJ NO.	SHEET NO.
8	N.D.	F-1-094(007)920	S-11



FHWA REGION	STATE	FED. AID PROJ NO.	SHEET NO.
8	N.D.	F-1-094(007)920	S-12



Sta 176+82-21' Lt.
Northbound, South
Approach Cross Section

TRAFFIC CONTROL SYSTEM
Signal Standard Details

MEMORIAL HWY & EAST RAMP
MANDAN, ND


QUANTITIES

(A) Used for internal wiring of signal standard.

TRAFFIC CONTROL SYSTEM Summary of Quantities

Memorial Hwy & East Ramp
Mandan, ND

FHWA REGION	STATE	FED. AID PROJ. NO.	HEET NO.
8	N.D.	F-1-094(007)920	5-14



STATION	CONDUIT RUNS		CABLE RUNS			FHWA REGION	STATE	FED AID PROJ. NO.	SHEET NO.
	Length	Size	Length	Type					
0+24-28' Rt. to	227'	1" (A)	618'	Loop Lead In					
2+44-80' Rt. to	74	1"							
3+10-107' Rt. to	37'	2"							
3+03-70' Rt. to	23'	2" (B)							
3+00-46' Rt. to	92'	2" (B)							
3+79-60' Rt. to	26'	2½" (B)							
3+73-38' Rt. to	83'	3" (B)							
3+73-43' Lt. to	18'	3" (B)							
3+83-60' Lt.									
2+32-5.5' Lt	35'	2" (B)	213'	Loop Lead In					
2+53-33' Lt.	58'	2½" (B)							
3+03-42' Lt.	93'	3" (B)							
3+83-60' Lt.									

QUANTITIES						
Loop Lead-In Conductor	Detector Polyethylene Conduit Pre-wired	Saw Slot	Relocate Pull Box	1" Dia. Rigid Conduit	2" Dia. Rigid Conduit	
LF	LF	LF	EA	LF	LF	
831	242	52	1	74	37	

DETECTOR LOOPS

Loop No.	No. of Turns	Size	Type of Loop	Conductor LF	Saw Slot LF	Preformed Loop EA
1	3	6x6	Presence	136	26	
2	3	6x6	Presence	106	26	
3	4	6x6	Presence			(A)
4	4	6x6	Presence			(A)
5	4	6x6	Passage?			(A)

(A) Installed on structural plans

(B) Existing conduit

TRAFFIC CONTROL SYSTEM
Conduit and Conductor Quantities

I-94 Bus. Loop & Memorial Hwy.
Bismarck, ND

FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	SS-1

SIGN SUMMARY - PERFORATED TUB

BASIS OF ESTIMAT

Sign Support Length

The sign support lengths have been calculated using the following information:

VERTICAL CLARANCE

Signs Viewed From Mainline 84
Signs Viewed From Crossings 84

TRAFFIC CONTROL SYSTEM

Sign Summary

Memorial Highway
Mandan, ND

FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	F-1-094(007)920	SS-2

STATION	ASSEMBLY NUMBER	SIGN AREA FLAT SHEET TYPE 2 3 OR 4	SIGN SUMMARY - PERFORATED TUBE								TOTAL ANCHOR UNIT SUPPORT LNG. SIZE NO WEIGHT	RESET FOR SIGN SUP. PAN. SUP. SIZE	MAX. LNG. FOR SUP. SIZE	
			SIGN SUPPORT POST LENGTHS	1ST	2ND	3RD	4TH	SIGN SUPPORT SLEEVE LENGTH	1ST	2ND	3RD	4TH		
0+65RT	TRUCK		RESET ON LIGHT STANDARD										4.0 2.50 1 39.60	1 1 1 10.8
3+18LT	9RS			9.8										
5+53RT	15RS		RESET ON LIGHT STANDARD											
5+76RT	YIELD												39.60	4 1
TOTAL NO.	2	0.00 0.00												

BASIS OF ESTIMATE
Sign Support Lengths

The sign support lengths have been calculated using the following information:

VERTICAL CLEARANCE

Signs Viewed From Mainline	84"
Signs Viewed From Crossings	84"

TRAFFIC CONTROL SYSTEM
Sign Summary

Memorial Highway
Mandan, ND


FORM REGION	STATE	FED AIO PROJ NO	SHEET NO
8	N.D.	IR-194-4(053)000	SS-3

SIGN QUANTITIES FOR ROUND STEEL SUPPORTS


Station	Steel Supports								Breakaway Bases		Foundation							
	Sign or Assembly Number	Overlay Panel	Type 2 4 Panel	Type 3 & Post	Length Post	Length Post	Nominal Post Dia.	Wall Thickness	Directional 3.5"	Stub Post 3.5"	Dia.	Depth	C.Y	Fuse Joints	Reset Sign Panel	Reset Sign Support	Revise Sign Panel	
169+95 Lt.	Sign No.1		30	12.0	12.0	3.5"	.226	218.64	2		1'4"	6'6"	.68	2	1			
169+98 Rt.									2		1'4"	6'6"	.68		1	2	2	
12+55 Lt.									1		1'4"	7'6"	.39		1	1		
172+00 Rt.									1		1'4"	7'6"	.39		1	1		
175+90 Rt.									2		1'4"	6'6"	.68		1	2	2	
176+82 Lt.									2		1'4"	6'6"	.68		1	2	2	
0+20 Rt.									1		1'4"	6'6"	.34		1	1		
0+45 Lt.									1		1'4"	6'6"	.34		1	1		
TOTALS			30					218.64	2		10		4.18	2	8	10	6	

TRAFFIC CONTROL SYSTEM
Round Steel Support
Sign Summary


Memorial Highway
Mandan, ND




FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	55-5



FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	55-6



FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	53-7



FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	SS-8

OVERHEAD SIGN STRUCTURE 94' TRUSS
Sta. 179+79 Surv. 1 Ea.

INSTALL CLASS AE CONCRETE SIGN FOUNDATIONS
Sta. 179+79 Surv. Rt. & Lt. 16.11 CY

RESET SIGN PANEL (Overhead Structure Mounted)


From 176+75 W. Bd. Surv.

To


179+79 Surv. Lt. 1 EA

Sta. 179+79 Surv. Lt.

Reset Sign on Overhead Sign
Structure From Sta. 176+75 W. Bd. Surv.



Bismarck Expy
McKenzie Dr
Memorial Hwy
Mandan



PLASTIC PAVEMENT MARKING FILM LINE

4" White Lane Lines, 10' Line, 30' Skip
Dbl. 4" Yellow Barrier Line (3" Between)
8" White Channel Line
8" Yellow Lines - 5' Centers @ 45°, Cross Hatch Lines
4" Yellow Median Island Edge Line

Total 387 SF

PAVEMENT MARKING PAINTED LINE

Curb Markings, top and face yellow 131LF


TRAFFIC CONTROL SYSTEM
Signing & Pavement Marking
Layout

Memorial Highway
Mandan, ND



FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	SS-9

N

Sta. 182+80 Lt.
Assembly 20 WS
Light Std. Mtd.



W3-3-36



Remove
(Light Std. Mtd.)


PLASTIC PAVEMENT MARKING FILM-LINE

Dbl. 4" Yellow Barrier Lines (3" Between) 227 SF

TRAFFIC CONTROL SYSTEM
Signing & Pavement Marking Layout

Memorial Highway
Mandan, ND


FHWA REGION	STATE	FED. AID PROJ. NO.	HEET NO.
8	N.D.	IR-194-4(053)000	55.10



FHWA REGION	STATE	FED AID PROJ NO	HEET NO
8	N.D.	ZR-194-4(053)00955-11	

RESET SIGN PANEL


Sta. 44+66 M.L.
Overlay Sign



Sign No. 5



From Sta. 44+66 M.L. To Sta. 66+75 M.L. 1 EA

Sta. 40+10 E, Serv.Road
Cut Posts to
Required Length.



Remove


In Place
To Remain




Sign No. 4

Sta. 44+66 M.L.
Overlay Sign

Sta. 66+75 M.L.
Remove Top Sign &
Reset Bottom Sign 1'-3" Higher.



Remove
Reset



Sign No. 5

Sta. 66+75 M.L.
Overlay Sign

OVERLAY PANEL TYPE 3A REFLECTIVE SHEETING

Sign No. 4	117.0 SF
Sign No. 5	117.0 SF
Sign No. 6	97.5 SF
Total	331.5 SF

TRAFFIC CONTROL SYSTEM
Signing Layout

Bismarck Expressway
Mandan, N.D.

FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4 (053) 000	55-12




Sta. 102+00 Lt.
Cut Posts to
Required Length.

To Memorial Hwy

Remove

Mckenzie Dr
Mandan
3/4 MILE

In Place
To Remain



$$\begin{array}{l} \text{Equation} \\ 107+29.9 \text{ Bk.} = \\ 7+86.88 \text{ Ahd.} \end{array}$$


TRAFFIC CONTROL SYSTEM
Signing Layout

Bismarck Expressway
Bismarck, N.D.


FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	F-1-094(007)920	55-13

TRAFFIC CONTROL SYSTEM
Signing & Pavement Marking Layout

Memorial Highway
Bismarck, ND




FHWA REGION	STATE	FED. AID PROJ. NO.	SHEET NO.
8	N.D.	IR-194-4(053)000	55-14




(New)

Sta. 3+42 S.E. Ramp
Sign No. 2
Area = 162.0 SF




(overlay)

Sta. 169+95 Lt. w. Bd. Surv.
Sign No. 1
Area = 30.0 SF




(overlay)

Sta. 44+66 M.L.
Sign No. 4
Area = 117.0 SF




(New)

Sta. 3+42 S.E. Ramp
Sign No. 3
Area = 117.0 SF



(overlay)

Sta. 66+75 M.L.
Sign No. 6
Area = 97.5 SF



(overlay)

Sta. 44+66 M.L.
Sign No. 5
Area = 117.0 SF

NOTE: All signs on this sheet have green background with white border and legend, Type 3A. All letters shall be Series E modified.

TRAFFIC CONTROL SYSTEM

Sign Detail Sheet

Bismarck Expressway
Memorial Highway
Mandan, ND